

COMUNITY SOFTENER



Unique features

- Fully automatic microprocessor-controlling operation
- Display - Current time, Remaining soft water & current flow
- Inbuilt brine tank, brine valve and float assembly
- BFT Technology helps to make fully automated operation with pump, water level controller and softener
- Incorporated with pressure relief and water sample valve
- Can be use before soft water storage tank
- Can be use for entire apartment, colony.



Model wise Specification

	200R 63608	300R 63610	500R 63610	700R 63610	1000R 63610
Max. Flow Rate in LPH	: 6000 LPH	: 9000 LPH	: 9000 LPH	: 9000 LPH	: 9000 LPH
OBSA (Basis On 200ppm)	: 172000 Ltr	: 260000 Ltr	: 300000 Ltr	: 960000 Ltr	: 675000 Ltr
OBR (Basis On 200ppm)	: 43000 Ltr	: 65000 Ltr	: 100000 Ltr	: 160000 Ltr	: 225000 Ltr
MPV Model	: 63608 BFT	: 63610 BFT	: 63610 BFT	: 63610 BFT	: 65610 BFT
Resin Tank Volume in Liter	: 210 Ltr	: 360 Ltr	: 530 Ltr	: 830 Ltr	: 1200 Ltr
Resin	: 175 Ltr	: 275 Ltr	: 425 Ltr	: 650 Ltr	: 900 Ltr
Salt Tank	: 200 Ltr	: 350 Ltr	: 500 Ltr	: 1000 Ltr	: 1000 Ltr
Salt Required / Regeneration	: 27 kg	: 42 kg	: 64 kg	: 98 Kg	: 135 kg
Salt Qty. / OBSA	: 108 kg	: 168 kg	: 192 kg	: 588 Kg	: 405 kg
Working Pressure	: 0.15 - 0.6 MPA	: 0.15 - 0.6 MPA	: 0.15 - 0.6 MPA	: 0.15 - 0.6 MPA	: 0.15 - 0.6 MPA
Inlet Outlet size	: 1.5"	: 2"	: 2"	: 2"	: 2"
Dimensions in mm	: L1000 x W550 x H1960	: L1445 x W1065 x H2140	: L1585 x W1145 x H2390	: L2000 x W1350 x H2390	: L2150 x W1425 x H2390